

Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II,  
as amended by Regulation (EU) No. 2020/878 - Europe

**Product:**  
**EPOXY BV Comp. A**

Version 1.07 / 13.11.2023

Replaces all previous versions

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1 Product identifier

Product name: EPOXY BV Comp. A

Product type: base for multi-component product

### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Field of application: buildings and metal industry

Ready-for-use mixture: Component

Identified uses: Consumer applications, Professional applications.

### 1.3 Details of the supplier of the safety data sheet

Company: PINTURAS KILNHER

Address: Pol. Ind. La Figuera, C/LLanterners, 44. 46394

City: ALACUAS

Province: VALENCIA

Telephone: (+34) 961 505 024

Fax: (+34) 961 505 024

E-mail: kilnher@kilnher.com

Web: www.kilnher.com

### 1.4 Emergency telephone number

(+34) 961 505 024 (Only available during office hours; Monday-Friday; 07:00-15:00)

## SECTION 2: Hazards identification

### 2.1 Classification of the substance or mixture

Product definition: Mixture

**Classification according to Regulation (EC) No. 1272/2008 [CLP]**

Hazard class	Hazard category	Indications of danger
Skin corrosion/irritation	2	H315
Serious eye damage/eye irritation	2	H319
Skin sensitisation	1	H317
Aquatic Hazard (Long-Term)	2	H411 Aquatic Chronic

\*See Section 11 for more detailed information on health effects and symptoms.

## 2.2 Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

### Hazard pictograms (CLP)



### Signal word (CLP)

Warning

### Hazard statements (CLP)

**H315** - Causes skin irritation.

**H317** - May cause an allergic skin reaction.

**H319** - Causes serious eye irritation.

**H411** - Toxic to aquatic life with long lasting effects.

### Precautionary statements (CLP)

**General:** Keep out of reach of children. If medical advice is needed, have product container or label at hand.

**Prevention:** Wear protective gloves. Wear eye or face protection. Avoid release to the environment. Avoid breathing vapor. Wash thoroughly after handling.

**Response:** Collect spillage. Take off contaminated clothing and wash it before reuse.

**IF ON SKIN:** Wash with plenty of water. If skin irritation or rash occurs: Get medical advice or attention.

**IF IN EYES:** Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice or attention.

**Disposal:** Dispose of contents and container in accordance with all local, regional, national and international regulations.

**Hazardous ingredients:** bisphenol A-(epichlorhydrin) epoxy resin MW =< 700

**Supplemental label elements:** Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist. Contains epoxy constituents. May produce an allergic reaction.

### Special packaging requirements

**Containers to be fitted with child-resistant fastenings:** Not applicable.

**Tactile warning of danger:** Not applicable

## 2.3 Other hazards

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

Other hazards which do not result None known.

## SECTION 3: Composition/information on ingredients

### 3.1 Substances

Not applicable

### 3.2 Mixtures

Product/ingredient name	Identifiers	%	Regulation (EC) No. 1272/2008 [CLP]
bisphenol A-(epichlorhydrin) epoxy resin MW =< 700 [1]	REACH #: 01-2119456619-26 EC: 216-823-5 CAS: 1675-54-3 Index: 603-074-00-8	≥50 - ≤75	Skin Irrit. 2, H315 Skin Irrit. 2, H315: C ≥ 5% Eye Irrit. 2, H319 Eye Irrit. 2, H319: C ≥ 5% Skin Sens. 1, H317 Aquatic Chronic 2, H411
dipropylene glycol dibenzoate [1]	REACH #: 01-2119529241-49 EC: 248-258-5 CAS: 27138-31-4	≥3 - ≤5	Aquatic Chronic 3, H412
4,4'-isopropylidenediphenol [1] [2] [3]	REACH #: 01-2119457856-23 EC: 201-245-8 CAS: 80-05-7 Index: 604-030-00-0	<0.1	Eye Dam. 1, H318 M [Acute] = 1 Skin Sens. 1, H317 M [Chronic] = 10 Repr. 1B, H360F STOT SE 3, H335 Aquatic Acute 1, H400 Aquatic Chronic 1, H410

\* See Section 16 for the full text of the H statements declared above.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

#### Type

[1] Substance classified with a health or environmental hazard

[2] Substance with a workplace exposure limit, see section 8.

[3] Substance of equivalent concern.

[\*] The classification as a carcinogen by inhalation applies only to mixtures placed on the market in powder form containing 1% or more of titanium dioxide particles with aerodynamic diameter ≤ 10 µm not bound within a matrix.

## SECTION 4: First aid measures

### 4.1 Description of first aid measures

#### General

In all cases of doubt, or when symptoms persist, seek medical attention. Never give anything by mouth to an unconscious person.

If breathing is irregular, drowsiness, loss of consciousness or cramps: Call 112 and give immediate treatment (first aid).

**Eye contact**

Check for and remove any contact lenses. Immediately flush eyes with plenty of water for at least 15 minutes, occasionally lifting the upper and lower eyelids. Seek immediate medical attention/advice.

**Inhalation**

Remove to fresh air and keep at rest in a position comfortable for breathing. Give nothing by mouth. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. If unconscious, place in recovery position and get medical attention immediately.

**Skin contact**

Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognized skin cleanser. Do NOT use solvents or thinners.

**Ingestion**

If swallowed, seek medical advice immediately and show this container or label. Keep person warm and at rest. Do not induce vomiting unless directed to do so by medical personnel. Lower the head so that vomit will not re-enter the mouth and throat.

**Protection of first-aiders**

No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.

Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

**4.2 Most important symptoms and effects, both acute and delayed**

**Potential acute health effects**

**Eye contact**

Causes serious eye irritation.

**Inhalation**

No known significant effects or critical hazards.

**Skin contact**

Causes skin irritation. May cause an allergic skin reaction.

**Ingestion**

No known significant effects or critical hazards.

**Over-exposure signs/symptoms**

**Eye contact**

Adverse symptoms may include the following: pain or irritation watering redness.

**Inhalation**

No specific data.

**Skin contact**

Adverse symptoms may include the following: irritation redness.

**Ingestion**

No specific data.

**4.3 Indication of any immediate medical attention and special treatment needed**

Notes to physician: Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.

Specific treatments: No specific treatment.

## SECTION 5: Firefighting measures

### 5.1 Extinguishing media

**Extinguishing media :** Recommended: alcohol resistant foam, CO<sub>2</sub>, powders, water spray.  
Not to be used: waterjet.

### 5.2 Special hazards arising from the substance or mixture

**Hazards from the substance or heated, mixture:** In a fire or if heated, a pressure increase will occur and the container may burst. This material is toxic to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.

**Hazardous combustion products:** Decomposition products may include the following materials: carbon oxides metal oxide/oxides.

### 5.3 Advice for firefighters

Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Fire will produce dense black smoke. Exposure to decomposition products may cause a health hazard. Cool closed containers exposed to fire with water. Do not release runoff from fire to drains or watercourses. Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.

## SECTION 6: Accidental release measures

### 6.1 Personal precautions, protective equipment and emergency procedures

Avoid all direct contact with the spilled material. Exclude sources of ignition and be aware of explosion hazard. Ventilate the area. Avoid breathing vapor or mist. Refer to protective measures listed in sections 7 and 8. No action shall be taken involving any personal risk or without suitable training. If the product contaminates lakes, rivers, or sewers, inform the appropriate authorities in accordance with local regulations.

### 6.2 Environment related measures

Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities.

### 6.3 Methods and materials for containment and cleaning up

Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with noncombustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Contaminated absorbent material may pose the same hazard as the spilled product.

### 6.4 Reference to other sections

See Section 1 for emergency contact information.  
See Section 8 for information on appropriate personal protective equipment. See Section 13 for additional waste treatment information.

## SECTION 7: Handling and storage

### 7.1 Precautions for safe handling

Contains epoxy constituents. Avoid all possible skin contact with epoxy and amine containing products, they may cause allergic reactions. Avoid inhalation of vapour, dust and spray mist. Avoid contact with skin and eyes. Eating, drinking and smoking should be prohibited in area where this material is handled, stored and processed. Appropriate personal protective equipment: see Section 8. Always keep in containers made from the same material as the original one.

### 7.2 Conditions for safe storage, including any incompatibilities

Store in accordance with local regulations. Store in a cool, well-ventilated area away from incompatible materials and ignition sources. Keep out of the reach of children. Keep away from: Oxidizing agents, strong alkalis, strong acids. No smoking. Prevent unauthorized access. Containers that are opened must be carefully resealed and kept upright to prevent leakage.

### 7.3 Specific end use(s)

See separate Product Data Sheet for recommendations or industrial sector specific solutions.

## SECTION 8: Exposure controls/personal protection

### 8.1 Control parameters

Product/ingredient name	Exposure limit values
4,4'-isopropylidenediphenol	<b>EU OEL (Europe, 1/2022).</b> TWA: 2 mg/m <sup>3</sup> 8 hours. Form: Inhalable fraction

#### 8.1.1 Recommended monitoring procedures

If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres - General requirements for the performance of procedures for the measurement of chemical agents) Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

#### 8.1.2 Derived effect levels

Not applicable

#### 8.1.3 Predicted effect concentrations

Not applicable

## 8.2 Exposure controls

Arrange sufficient ventilation by local exhaust ventilation and good general ventilation to keep the airborne concentrations of vapors or dust lowest possible and below their respective threshold limit value. Ensure that eyewash stations and safety showers are proximal to the workstation location.

### General

Gloves must be worn for all work that may result in soiling. Apron/coveralls/protective clothing must be worn when soiling is so great that regular work clothes do not adequately protect skin against contact with the product. Safety eyewear should be used when there is a likelihood of exposure.

### Hygiene measures

Wash hands, forearms, and face thoroughly after handling compounds and before eating, smoking, using lavatory, and at the end of day.



### Eye/face protection

Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles.



### Hand protection

Wear chemical-resistant gloves (tested to EN374) in combination with 'basic' employee training. The quality of the chemical-resistant protective gloves must be chosen as a function of the specific workplace concentrations and quantity of hazardous substances.

Since the actual work situation is unknown. Supplier of gloves should be contacted in order to find the appropriate type. Below listed glove(s) should be regarded as generic advice:

Recommended: Silver Shield / Barrier / 4H gloves, nitrile rubber, butyl rubber, Viton®

Short term exposure: neoprene rubber, natural rubber (latex), polyvinyl alcohol (PVA), polyvinyl chloride (PVC)

### Body protection

Personal protective equipment for the body should be selected based on the task being performed and the risks involved handling this product.

### Respiratory protection

Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. Wear appropriate respirator when ventilation is inadequate. Be sure to use approved/certified respirator or equivalent. It is not possible to specify precise filter type, since the actual work situation is unknown. Supplier of respirators should be contacted in order to find the appropriate filter.

### 8.2.1 Environmental exposure controls

Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

## SECTION 9: Physical and chemical properties

### 9.1 Information on basic physical and chemical properties

**Physical state:** VOC content, Ready-for-use mixture:  
Liquid.

**Colour:** Pink

**Odour:** Amine-like

**pH:** Testing not relevant or not possible due to nature of the product.

**Melting point/freezing point:** -16°C This is based on data for the following ingredient: bisphenol A-(epichlorhydrin) epoxy resin MW = < 700

**Boiling point/boiling range:** cTesting not relevant or not possible due to nature of the product.

**Flash point:** Closed cup: 110°C (230°F)

**Evaporation rate:** Testing not relevant or not possible due to nature of the product.

**Flammability:** Not available

**Upper/lower flammability or explosive limits:**  
No specific data.

**Vapour pressure:** 0 kPa This is based on data for the

following ingredient: bisphenol A-(epichlorhydrin) epoxy resin MW = < 700

**Vapour density:** Testing not relevant or not possible due to nature of the product.

**Specific gravity:** 1.5 g/cm<sup>3</sup>

**Partition coefficient (LogKow):** Testing not relevant or not possible due to nature of the product.

**Auto-ignition temperature:** Lowest known value: >400°C (>752°F) (dipropylene glycol dibenzoate).

**Decomposition temperature:** Testing not relevant or not possible due to nature of the product.

**Viscosity:** Testing not relevant or not possible due to nature of the product.

**Explosive properties:** Testing not relevant or not possible due to nature of the product.

**Oxidizing properties:** Testing not relevant or not possible due to nature of the product.

### 9.2 Other information

**Solvent(s) % by weight:** Weighted average: 1 %

**Water % by weight:** Weighted average: 0 %

**VOC content:** <10 g/l (Measured) 26.3 g/l

**Solvent Gas:** Weighted average: 0.005 m<sup>3</sup>/l

## SECTION 10: Stability and reactivity

### 10.1 Reactivity

No specific test data related to reactivity available for this product or its ingredients.

### 10.2 Chemical stability

The product is stable.

### 10.3 Possibility of hazardous reactions

Under normal conditions of storage and use, hazardous reactions will not occur.

### 10.4 Conditions to avoid

No specific data.

### 10.5 Incompatible materials

No specific data..

### 10.6 Hazardous decomposition products

When exposed to high temperatures (i.e. in case of fire) harmful decomposition products may be formed:

Decomposition products may include the following materials: carbon oxides halogenated compounds metal oxide/oxides



## SECTION 11: Toxicological information

### 11.1 Information on hazard classes as defined in Regulation (EC) No 2020/878

Epoxy and amine containing products can cause skin disorders such as allergic eczema. The allergy may arise after only a short exposure period.

#### 11.1.1 Acute toxicity

Product / ingredient name	Result	Species	Dose	Exposure
bisphenol A-(epichlorhydrin) epoxy resin MW =< 700	LD50 Dermal	Rabbit	>2000 mg/kg	-
	LD50 Dermal	Rat	>2000 mg/kg	-
	LD50 Oral	Rat	>2000 mg/kg	-
titanium dioxide	LC50 Inhalation Dusts and mists	Rat	>6.8 mg/l	4 hours
	LD50 Dermal	Rabbit	>5000 mg/kg	-
	LD50 Oral	Rat	>5000 mg/kg	-
dipropylene glycol dibenzoate	LC50 Inhalation Dusts and mists	Rat	>200 mg/l	4 hours
	LD50 Dermal	Rat	>2000 mg/kg	-
	LD50 Oral	Rat	3914 mg/kg	-
4,4'-isopropylidenediphenol	LD50 Dermal	Rabbit	>2000 mg/kg	-
	LD50 Oral	Rat	3250 mg/kg	-
	LD50 Oral	Rat	3250 mg/kg	-

#### 11.1.2 Acute toxicity estimates

Product / ingredient name	Oral mg/kg	Dermal mg/kg	Inhalation (gases) ppm	Inhalation (vapors) mg/l	Inhalation (dusts and mists) mg/l
dipropylene glycol dibenzoate	3914	-	-	-	-
4,4'-isopropylidenediphenol	3250	-	-	-	-

**11.1.3 Irritation/Corrosion**

Product / ingredient name	Result	Species	Score	Exposure
bisphenol A-(epichlorhydrin) epoxy resin MW =< 700	Eyes - Mild irritant	Rabbit	-	-
	Skin - MILD irritant	Rabbit	-	-
titanium dioxide	Skin - Mild irritant	Human	-	72 hours 300 Micrograms Intermittent
dipropylene glycol dibenzoate	Eyes - Mild irritant	Rabbit	-	-
	Skin - Mild irritant	Rabbit	-	-
4,4'-isopropylidenediphenol	Eyes - Severe irritant	Rabbit	-	24 hours 250 milligrams
	Skin - Mild irritant	Rabbit	-	24 hours 500 milligrams

**11.1.4 Sensitizer**

Product / ingredient name	Route of exposure	Species	Result
bisphenol A-(epichlorhydrin) epoxy resin MW =< 700	Skin	Guinea pig	Sensitizing

Sensitization : Contains bisphenol A-(epichlorhydrin) epoxy resin MW =< 700. May produce an allergic reaction.

**11.1.5 Mutagenic effects**

No known significant effects or critical hazards.

**11.1.6 Carcinogenicity**

No known significant effects or critical hazards.

**11.1.7 Reproductive toxicity**

No known significant effects or critical hazards.

**11.1.8 Teratogenic effects**

No known significant effects or critical hazards.

**11.1.9 Specific target organ toxicity (single exposure)**

Product / ingredient name	Category	Route of exposure	Target organs
4,4'-isopropylidenediphenol	3	-	Respiratory tract irritation

**11.1.10 Specific target organ toxicity (repeated exposure)**

Product / ingredient name	Category	Route of exposure	Target organs
No known data available in our database.	-	-	-

### 11.1.11 Aspiration hazard

Product / ingredient name	Result
No known data available in our database.	-

### 11.1.12 Information on the likely routes of exposure

Routes of entry anticipated: Oral, Dermal, Inhalation.

### 11.1.13 Potential chronic health effects

No known significant effects or critical hazards.

## 11.2 Information on other hazards

Endocrine disrupting properties: See Section 15 for details.

Other information: No additional known significant effects or critical hazards.

## SECTION 12: Ecological information

### 12.1 Toxicity

Do not allow to enter drains or watercourses. Toxic to aquatic life with long lasting effects.

Product / ingredient name	Result	Species	Exposure
bisphenol A-(epichlorhydrin) epoxy resin MW =< 700	Acute EC50 >11 mg/l	Algae	72 hours
	Acute EC50 1.8 mg/l	Daphnia	48 hours
	Acute LC50 2 mg/l	Fish	96 hours
titanium dioxide	Acute LC50 >100 mg/l	Daphnia	48 hours
	Acute LC50 >100 mg/l	Fish	96 hours
dipropylene glycol diben- zoate	Acute LC50 4.9 mg/l	Algae	72 hours
	Acute LC50 19.3 mg/l	Daphnia	48 hours
	Acute LC50 3.7 mg/l	Fish	96 hours
4,4'-isopropylidenediphenol	Acute LC50 7.5 mg/l	Fish	96 hours
	Chronic NOEC 0.8 mg/l Fresh water	Daphnia - Daphnia magna - Neonate	21 days
	Chronic NOEC 0.2 - 20 ppb Fresh water	Fish - Xiphophorus he- lleri - Juvenile (Fledgling, Hatchling, Weanling)	60 days

## 12.2 Persistence and degradability

Product / ingredient name	Test	Result	Dose	Inoculum	Aquatic half-life	Photolysis	Biodegradability
bisphenol A-(epichlorhydrin) epoxy resin MW =< 700	OECD 302B Inherent Biodegradability: Zahn-Wellens/EMPA Test	12 % - Not readily - 28 days	-	-	-	-	Not readily
dipropylene glycol dibenzoate	-	87 % - Readily - 28 days	-	-	-	-	Readily
4,4'-isopropylidenediphenol	-	1 - 2 % - Not readily - 28 days	-	-	-	-	Not readily

## 12.3 Bioaccumulative potential

Product / ingredient name	LogPow	BCF	Potential
bisphenol A-(epichlorhydrin) epoxy resin MW =< 700	2.64 - 3.78	31	low
dipropylene glycol dibenzoate	3.9	-	low
4,4'-isopropylidenediphenol	3.4	20 - 67	low

## 12.4 Mobility in soil

Soil/water partition coefficient ( $K_{oc}$ ): No known data available in our database.

Mobility: No known data available in our database.

## 12.5 Results of PBT and vPvB assessment

Product/ingredient name **PBT, P, B, T, vPvB, vP, vB.**

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

## 12.6 Endocrine disrupting properties

See Section 15 for details.

## 12.7 Other adverse effects

No known significant effects or critical hazards.

## SECTION 13: Disposal considerations

### 13.1 Waste treatment methods

The generation of waste should be avoided or minimized wherever possible. Residues of the product is listed as hazardous waste. Dispose of according to all state and local applicable regulations. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Spillage, remains, discarded clothes and similar should be discarded in a fireproof container.

European waste catalogue no. (EWC) is given below.







European waste catalogue (EWC) : 08 01 11\*

### Packaging

The generation of waste should be avoided or minimized wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.

## SECTION 14: Transport information

Transport may take place according to national regulation or ADR for transport by road, RID for transport by train, IMDG for transport by sea, IATA for transport by air.

	14.1 UN / ID no.	14.2 Proper shipping name	14.3 Transport ha- zard class(es)	14.4 PG*	14.5 Env*	Additional information
ADR/RID Class	UN3082	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (bisphenol A-(epi-chlorhydrin) epoxy resin MW =< 700)	9  	III	Yes.	This product is not regulated as a dangerous good when transported in sizes of ≤5 L or ≤5 kg, provided the packagings meet the general provisions of 4.1.1.1, 4.1.1.2 and 4.1.1.4 to 4.1.1.8. Tunel code: -
IMDG Class	UN3082	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.. (bisphenol A-(epi-chlorhydrin) epoxy resin MW =< 700)	9  	III	Yes.	This product is not regulated as a dangerous good when transported in sizes of ≤5 L or ≤5 kg, provided the packagings meet the general provisions of 4.1.1.1, 4.1.1.2 and 4.1.1.4 to 4.1.1.8. Emergency schedules: F-A, S-F
IATA Class	UN3082	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (bisphenol A-(epi-chlorhydrin) epoxy resin MW =< 700)	9  	III	Yes.	This product is not regulated as a dangerous good when transported in sizes of ≤5 L or ≤5 kg, provided the packagings meet the general provisions of 5.0.2.4.1, 5.0.2.6.1.1 and 5.0.2.8.

PG\* : Packing group

Env.\* : Environmental hazards

## 14.6 Special precautions for user

**Transport within user's premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

## 14.7 Maritime transport in bulk according to IMO instruments

Not applicable

## SECTION 15: Regulatory information

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

EU Regulation (EC) No. 1907/2006 (REACH) Annex XIV - List of substances subject to authorization - Substances of very high concern

#### Annex XIV

None of the components are listed

Substances of very high concern				
Ingredient name	Intrinsic property	Status	Reference number	Date of revision
4,4'-isopropylidenediphenol	Toxic to reproduction	Recommended	ED/01/2018	10/1/2019
4,4'-isopropylidenediphenol	Endocrine disrupting properties for human health	Recommended	ED/01/2018	10/1/2019
4,4'-isopropylidenediphenol	Endocrine disrupting properties for human health	Recommended	ED/01/2018	10/1/2019

#### Annex XVII

Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles  
Not applicable.

#### Other EU regulations

Seveso category This product is controlled under the Seveso III Directive.

#### Seveso category

E2: Hazardous to the aquatic environment - Chronic 2

### 15.2 Chemical Safety Assessment

Not applicable.

## SECTION 16: Other information

### 16.1 Abbreviations and acronyms

**ATE** Acute Toxicity Estimate

**CLP** Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008]

**EUH statement** CLP-specific Hazard statement

**RRN** REACH Registration Number

**DNEL** Derived No Effect Level

**PNEC** Predicted No Effect Concentration

### 16.2 Full text of abbreviated H statements : Full text of classifications [CLP/GHS]

H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H335	May cause respiratory irritation.
H351	Suspected of causing cancer.
H360F	May damage fertility.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.

Aquatic Acute 1	Category 1	AQUATIC HAZARD (ACUTE)
Aquatic Chronic 1	Category 1	AQUATIC HAZARD (LONG-TERM)
Aquatic Chronic 2	Category 2	AQUATIC HAZARD (LONG-TERM)
Aquatic Chronic 3	Category 3	AQUATIC HAZARD (LONG-TERM)
Carc. 2	Category 2	CARCINOGENICITY
Eye Dam. 1	Category 1	SERIOUS EYE DAMAGE/ EYE IRRITATION
Eye Irrit. 2	Category 2	SERIOUS EYE DAMAGE/ EYE IRRITATION
Repr. 1B	Category 1B	TOXIC TO REPRODUCTION
Skin Irrit. 2	Category 2	SKIN CORROSION/IRRITATION
Skin Sens. 1	Category 1	SKIN SENSITIZATION
Skin Sens. 1	Category 1A	SKIN SENSITIZATION
STOT SE 3	Category 3	SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE)

### 16.3 Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Classification	Justification
SKIN CORROSION/IRRITATION	Calculation method
SERIOUS EYE DAMAGE/ EYE IRRITATION	Calculation method
SKIN SENSITIZATION	Calculation method
AQUATIC HAZARD (LONG-TERM)	Calculation method

### 16.4 Notice to reader

Indicates information that has changed from previously issued version.

The information contained in this safety data sheet is based on the present state of knowledge and EU and national legislation. It provides guidance on health, safety and environmental aspects for handling the product in a safe way and should not be construed as any guarantee of the technical performance or suitability for particular applications.

It is always the duty of the user/employer to ascertain that the work is planned and carried out in accordance with the national regulations.

## SECTION 17: Safe Use of Mixture Information

This document is intended to communicate the conditions of safe use for the product and should always be read in combination with the product's Safety Data Sheet and labels.

### 17.1 General description of the process covered

Indoor or outdoor spray painting by professionals or with brush, roller, putty knife, dipping etc. with good general room ventilation

**This safe use information is linked to:** Professional spray painting and/or low-energy painting, local effect - Level II  
Skin Sens. 1, Eye Irrit. 2, Asp. Tox. 1 or Solvent.

**Sector(s) of use:** Industrial uses - Professional uses

**Product category(ies):** Coatings and paints, thinners, paint removers

### 17.2 Operational conditions

**Place of use:** Indoor or outdoor use



**17.3 Risk management measures (RMM)**

Contributing activity	Process category (ies)	Maximum duration	Ventilation		Respiratory	Eye	Hands
			Type and air changes per hour				
Preparation of material for application	PROC05	More than 4 hours	Good general room ventilation - Outdoors	3 - 5	None	Use eye protection according to EN 166.	Wear suitable gloves tested to EN374.
Loading of application equipment and handling of coated parts before curing	PROC08a	More than 4 hours	Good general room ventilation - Outdoors	3 - 5	None	Use eye protection according to EN 166.	Wear suitable gloves tested to EN374.
Professional application of coatings by brush or roller	PROC10	More than 4 hours	Good general room ventilation - Outdoors	3 - 5	None	Use eye protection according to EN 166.	Wear suitable gloves tested to EN374.
Professional application of coatings by spraying	PROC11	More than 4 hours	Good general room ventilation - Outdoors	3 - 5	Wear a respirator conforming to EN140 with an assigned protection factor of at least 10.	Use eye protection according to EN 166.	Wear suitable gloves tested to EN374.
Film formation - force drying, stoving and other technologies	PROC04	More than 4 hours	Good general room ventilation - Outdoors	3 - 5	None	None	None
Cleaning	PROC05	More than 4 hours	Good general room ventilation - Outdoors	3 - 5	None	Use eye protection according to EN 166.	Wear suitable gloves tested to EN374.
Waste management	PROC08a	More than 4 hours	Good general room ventilation - Outdoors	3 - 5	None	Use eye protection according to EN 166.	Wear suitable gloves tested to EN374.

\*See chapter 8 of this Safety Data Sheet for specifications.

**17.4 Further information**

The information in this Safe Use of Mixture Information (SUMI) sheet is based on the data provided by the substance supplier for the substances in the product for which a chemical safety assessment has been carried out at the time of issue. It does not guarantee safe use of the product and does not replace any occupational risk assessment required by legislation. When developing workplace instructions for employees, SUMI sheets should always be considered in combination with the Safety Data Sheet (SDS) and the label of the product.

No liability is accepted for any damage, no matter of what kind, which is a direct or indirect consequence of acts and/or decisions based on the contents of this document.